

# FGPF4536

## 360 V PDP Trench IGBT

### Features



- High Current Capability
- Low Saturation Voltage:  $V_{CE(sat)} = 1.59 \text{ V @ } I_C = 50 \text{ A}$
- High Input Impedance
- Fast Switching
- RoHS Compliant

### Applications

- PDP TV, Consumer appliances, Lighting

### General Description

Using novel trench IGBT technology, Fairchild®'s new series of trench IGBTs offer the optimum performance for consumer appliances, PDP TV and lighting applications where low conduction and switching losses are essential.



### Absolute Maximum Ratings

Symbol	Description	Rated	Unit
$V_{CES}$	Collector to Emitter Voltage	360	V
$V_{GES}$	Gate to Emitter Voltage	$\pm 30$	V
$I_C \text{ pulse}(1)^*$	Pulsed Collector Current @ $T_C = 25^\circ\text{C}$	220	A
$P_D$	Maximum Power Dissipation @ $T_C = 25^\circ\text{C}$	28.4	W
	Maximum Power Dissipation @ $T_C = 100^\circ\text{C}$	11.4	W
$T_J$	Operating Junction Temperature	-55 to +150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-55 to +150	$^\circ\text{C}$
$T_L$	Maximum Lead Temp. for soldering Purposes, 1/8" from case for 5 seconds	300	$^\circ\text{C}$

### Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JC}(\text{IGBT})$	Thermal Resistance, Junction to Case	-	4.4	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	-	62.5	$^\circ\text{C/W}$

**Notes:**

(1) Half Sine Wave,  $D < 0.01$ , pulse width  $< 1 \mu\text{sec}$

\*  $I_{C\_pulse}$  limited by max  $T_J$

## Package Marking and Ordering Information

Device Marking	Device	Package	Packaging Type	Qty per Tube	Max Qty per Box
FGPF4536	FGPF4536TU	TO-220F	Tube	50ea	-

## Electrical Characteristics of the IGBT T<sub>C</sub> = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
<b>Off Characteristics</b>						
BV <sub>CES</sub>	Collector to Emitter Breakdown Voltage	V <sub>GE</sub> = 0V, I <sub>C</sub> = 250 μA	360	-	-	V
$\frac{\Delta BV_{CES}}{\Delta T_J}$	Temperature Coefficient of Breakdown Voltage	V <sub>GE</sub> = 0V, I <sub>C</sub> = 250 μA	-	0.4	-	V/°C
I <sub>CES</sub>	Collector Cut-Off Current	V <sub>CE</sub> = V <sub>CES</sub> , V <sub>GE</sub> = 0 V	-	-	100	μA
I <sub>GES</sub>	G-E Leakage Current	V <sub>GE</sub> = V <sub>GES</sub> , V <sub>CE</sub> = 0 V	-	-	±400	nA
<b>On Characteristics</b>						
V <sub>GE(th)</sub>	G-E Threshold Voltage	I <sub>C</sub> = 250 μA, V <sub>CE</sub> = V <sub>GE</sub>	2.4	3.3	4.0	V
V <sub>CE(sat)</sub>	Collector to Emitter Saturation Voltage	I <sub>C</sub> = 20 A, V <sub>GE</sub> = 15 V	-	1.19	-	V
		I <sub>C</sub> = 30 A, V <sub>GE</sub> = 15 V	-	1.33	-	V
		I <sub>C</sub> = 50 A, V <sub>GE</sub> = 15 V, T <sub>C</sub> = 25°C	-	1.59	1.8	V
		I <sub>C</sub> = 50 A, V <sub>GE</sub> = 15 V, T <sub>C</sub> = 125°C	-	1.66	-	V
<b>Dynamic Characteristics</b>						
C <sub>ies</sub>	Input Capacitance	V <sub>CE</sub> = 30 V, V <sub>GE</sub> = 0 V, f = 1MHz	-	1295	-	pF
C <sub>oes</sub>	Output Capacitance		-	56	-	pF
C <sub>res</sub>	Reverse Transfer Capacitance		-	43	-	pF
<b>Switching Characteristics</b>						
t <sub>d(on)</sub>	Turn-On Delay Time	V <sub>CC</sub> = 200 V, I <sub>C</sub> = 20 A, R <sub>G</sub> = 5 Ω, V <sub>GE</sub> = 15 V, Resistive Load, T <sub>C</sub> = 25°C	-	5	-	ns
t <sub>r</sub>	Rise Time		-	20	-	ns
t <sub>d(off)</sub>	Turn-Off Delay Time		-	41	-	ns
t <sub>f</sub>	Fall Time		-	182	-	ns
t <sub>d(on)</sub>	Turn-On Delay Time	V <sub>CC</sub> = 200 V, I <sub>C</sub> = 20 A, R <sub>G</sub> = 5 Ω, V <sub>GE</sub> = 15 V, Resistive Load, T <sub>C</sub> = 125°C	-	4.6	-	ns
t <sub>r</sub>	Rise Time		-	21	-	ns
t <sub>d(off)</sub>	Turn-Off Delay Time		-	43	-	ns
t <sub>f</sub>	Fall Time		-	249	-	ns
Q <sub>g</sub>	Total Gate Charge	V <sub>CE</sub> = 200 V, I <sub>C</sub> = 20 A, V <sub>GE</sub> = 15 V	-	47	-	nC
Q <sub>ge</sub>	Gate to Emitter Charge		-	5.4	-	nC
Q <sub>gc</sub>	Gate to Collector Charge		-	15	-	nC

## Typical Performance Characteristics

Figure 1. Typical Output Characteristics




Figure 2. Typical Output Characteristics




Figure 3. Typical Saturation Voltage Characteristics




Figure 4. Transfer Characteristics




Figure 5. Saturation Voltage vs. Case Temperature at Variant Current Level





Figure 6. Saturation Voltage vs. Vge



## Typical Performance Characteristics

Figure 7. Saturation Voltage vs.  $V_{GE}$




Figure 8. Capacitance Characteristics




Figure 9. Gate charge Characteristics




Figure 10. SOA Characteristics




Figure 11. Turn-on Characteristics vs. Gate Resistance






Figure 12. Turn-off Characteristics vs. Gate Resistance




### Typical Performance Characteristics


**Figure 13. Turn-on Characteristics vs. Collector Current**




**Figure 14. Turn-off Characteristics vs. Collector Current**




**Figure 15. Switching Loss vs. Gate Resistance**



**Figure 16. Switching Loss vs. Collector Current**




**Figure 17. Turn off Switching SOA Characteristics**




Typical Performance Characteristics

Figure 18. Transient Thermal Impedance of IGBT



**Package Dimensions**

**TO-220F (Retractable)**



- NOTES:**
- A. EXCEPT WHERE NOTED CONFORMS TO EIAJ SC91A.
  - B. DOES NOT COMPLY EIAJ STD. VALUE.
  - C. ALL DIMENSIONS ARE IN MILLIMETERS.
  - D. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR PROTRUSIONS.
  - E. DIMENSION AND TOLERANCE AS PER ASME Y14.5-1994.
  - F. OPTION 1 - WITH SUPPORT PIN HOLE.  
OPTION 2 - NO SUPPORT PIN HOLE.
  - G. DRAWING FILE NAME: TO220M03REV3


**\* Front/Back Side Isolation Voltage : AC 2700V**

Dimensions in Millimeters



**TRADEMARKS**

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

- |   |                         |   |                  |
|---|-------------------------|---|------------------|
| 2Cool™  | FPS™                    | PowerTrench®                                    | Sync-Lock™       |
| AccuPower™  | F-PFS™                  | PowerXS™  | SYSTEM GENERAL®* |
| AX-CAP®*  | FRFET®                  | Programmable Active Droop™                      | TinyBoost™       |
| BitSiC™   | Global Power ResourceSM | QFET®   | TinyBuck™        |
| Build it Now™   | Green Bridge™           | QS™   | TinyCalc™        |
| CorePLUS™   | Green FPS™              | Quiet Series™                                   | TinyLogic®       |
| CorePOWER™  | Green FPS™ e-Series™    | RapidConfigure™                                 | TINYOPTO™        |
| CROSSVOLT™  | Gmax™                   | GTO™  | TinyPower™       |
| CTL™  | IntelliMAX™             | ISOPLANAR™                                      | TinyPWM™         |
| Current Transfer Logic™   | ISOPLANAR™              | Marking Small Speakers Sound Louder and Better™ | TinyWire™        |
| DEUXPEED®   | MegaBuck™               | MICROCOUPLER™                                   | TranSiC®         |
| Dual Cool™  | MicroFET™               | MicroPak™                                       | TriFault Detect™ |
| EcoSPARK®   | MicroPak2™              | MillerDrive™                                    | TRUECURRENT®*    |
| EfficientMax™   | MotionMax™              | mWSaver™  | µSerDes™         |
| ESBC™   | OptoHiT™                | OPTOLOGIC®                                      | UHC®             |
|  | OPTOPLANAR®             | SPM®  | Ultra FRFET™     |
| Fairchild®  |                         | STEALTH™  | UniFET™          |
| Fairchild Semiconductor®  |                         | SuperFET®                                       | Vcx™             |
| FACT Quiet Series™  |                         | SuperSOT™-3                                     | VisualMax™       |
| FACT®   |                         | SuperSOT™-6                                     | VoltagePlus™     |
| FAST®   |                         | SuperSOT™-8                                     | XS™              |
| FastvCore™  |                         | SupreMOS®                                       |                  |
| FETBench™   |                         | SyncFET™  |                  |

\*Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

**DISCLAIMER**

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used here in:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**ANTI-COUNTERFEITING POLICY**

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.Fairchildsemi.com, under Sales Support. Counterfeiting of semiconductor parts is a growing problem in the industry. All manufactures of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

**PRODUCT STATUS DEFINITIONS**  
Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. I64