

E-Series RF 1:1 Transformer 2-500 MHz

Features


- Surface Mount
- 1:1 Impedance Ratio




Description

M/A-COM's ETC1-1T-5 is a 1:1 RF transformer in a low cost, surface mount package. Ideally suited for high volume cellular wireless applications. Typical applications include single to balanced mode conversion and impedance matching.

SM-22 Package



Schematic



Electrical Specifications @25°C

Parameter	Units	Typical	Minimum	Maximum
Frequency Range 2 - 500	MHz	_	_	_
Insertion Loss (f _L - f _U)				
2 - 500 MHz	dB	_	_	2.0
2 - 300 MHz	dB	_	_	1.0
Amplitude Imbalance				
2 - 300 MHz	dB	_	_	0.3
2 - 500 MHz	dB	_	_	0.6
Phase Imbalance				
2 - 300 MHz	o	_	_	2.0°
2 - 500 MHz	0	_	_	5.0°

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions ADVANCED: Data Sheets contain minimation regarding a product Mr. Com., simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

PRELIMINARY: Data Sheets contain information regarding a product MrA-COM Technology.

Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples a Commitment to produce in volume is not guaranteed.

- North America Tel: 800.366.2266 Europe Tel: +353.21.244.6400 India Tel: +91.80.43537383 China Tel: +86.21.2407.1588

Visit www.macomtech.com for additional data sheets and product information



Absolute Maximum Ratings

Parameter	Absolute Maximum		
RF Power	250 mW		
DC Current	30 mA		
Operating Temperature	-20°C to +85°C		
Storage Temperature	-20°C to +85°C		

Functional Configuration

Function	Pin No.
Secondary Dot	3
Secondary CT	_
Secondary	1
Primary	5
Primary Dot	4
Primary CT	_
Not Connected	2

typical. Mechanical outline has been fixed. Engineering samples and Commitment to produce in volume is not guaranteel.

North America Tel: 800.366.2266
 India Tel: +91.80.43537383
 Europe Tel: +353.21.244.6400
 China Tel: +86.21.2407.1588

Visit www.macomtech.com for additional data sheets and product information.