


Radar Pulsed Power Transistor
0.85W, 1.2-1.4 GHz, 2ms Pulse, 20% Duty

M/A-COM Products
Released, 30 May 07

Features

- NPN silicon microwave power transistors
- Common emitter configuration
- Broadband Class A operation
- High efficiency inter-digitized geometry
- Diffused emitter ballasting resistors
- Gold metallization system
- Internal input and output impedance matching
- Hermetic metal/ceramic package
- RoHS compliant

Outline Drawing



Absolute Maximum Ratings at 25°C

Parameter	Symbol	Rating	Units
Collector-Emitter Voltage	V_{CES}	27	V
Collector-Emitter Voltage	V_{CEO}	20	V
Emitter-Base Voltage	V_{EBO}	3.5	V
Collector Current (Peak)	I_C	0.71	A
Power Dissipation @ +25°C	P_{TOT}	9.2	W
Storage Temperature	T_{STG}	-65 to +200	°C
Junction Temperature	T_J	200	°C

Electrical Specifications: $T_C = 25 \pm 5^\circ\text{C}$ (Room Ambient)

Parameter	Test Conditions	Frequency	Symbol	Min	Max	Units
Collector-Emitter Breakdown Voltage	$I_C = 4\text{mA}$		BV_{CES}	27	-	V
Collector-Emitter Breakdown Voltage	$I_C = 10\text{mA}$		BV_{CEO}	20	-	V
Collector-Emitter Leakage Current	$V_{CE} = 15\text{V}$		I_{CES}	-	1.0	mA
Thermal Resistance	$V_{CC} = 11.5\text{V}$, $P_{in} = 0.1\text{W}$	$F = 1.2, 1.3, 1.4\text{ GHz}$	$R_{TH(JC)}$	-	19.0	°C/W
Output Power	$V_{CC} = 11.5\text{V}$, $P_{in} = 0.1\text{W}$	$F = 1.2, 1.3, 1.4\text{ GHz}$	P_{OUT}	0.85	-	W
Power Gain	$V_{CC} = 11.5\text{V}$, $P_{in} = 0.1\text{W}$	$F = 1.2, 1.3, 1.4\text{ GHz}$	G_P	9.3	-	dB
Collector Efficiency	$V_{CC} = 11.5\text{V}$, $P_{in} = 0.1\text{W}$	$F = 1.2, 1.3, 1.4\text{ GHz}$	η_C	30	-	%
Input Return Loss	$V_{CC} = 11.5\text{V}$, $P_{in} = 0.1\text{W}$	$F = 1.2, 1.3, 1.4\text{ GHz}$	RL	-	-9	dB
Load Mismatch Tolerance	$V_{CC} = 11.5\text{V}$, $P_{in} = 0.1\text{W}$	$F = 1.2, 1.3, 1.4\text{ GHz}$	VSWR-T	-	2:1	-
Load Mismatch Stability	$V_{CC} = 11.5\text{V}$, $P_{in} = 0.1\text{W}$	$F = 1.2, 1.3, 1.4\text{ GHz}$	VSWR-S	-	1.5:1	-

1

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.

PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 / Fax: 978.366.2266

• **Europe** Tel: 44.1908.574.200 / Fax: 44.1908.574.300

• **Asia/Pacific** Tel: 81.44.844.8296 / Fax: 81.44.844.8298

Visit www.macomtech.com for additional data sheets and product information.

M/A-COM Technology Solutions Inc and its affiliates reserve the right to make changes to the products or information contained herein without notice.

