



GLASS PASSIVATED SINGLE-PHASE BRIDGE RECTIFIER


GBPC1005 THRU GBPC110

FEATURES

- Plastic package has underwriters laboratory
- Flammability classification 94V-0
- Glass passivated ship junction
- High case dielectric with standing voltage of 1500V_{RMS}
- Typical I_R less than 0.1 μ A
- High surge current capability
- Ideal for printed circuit boards
- High temperature soldering guaranteed 260°C/10 seconds, 0.375" (9.5mm) lead length at 5 lbs (2.3kg) tension

MECHANICAL DATA

- Case: Epoxy, Molded Plastic body over passivated junctions
- Terminal: Plated leads solderable per MIL-STD-750 method 2026
- Mounting position: Any (Note 1)
- Weight: 0.1 ounce, 2.8 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified

		SYMBOLS	GBPC 1005	GBPC 101	GBPC 102	GBPC 104	GBPC 106	GBPC 108	GBPC 110	UNIT
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage		V _{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage		V _{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward output current at	T _C =60℃(Note2)	I _(AV)	3.0							Amps
	T _A =25℃(Note3)		2.0							
Peak Forward Surge Current single half sine-wave superimposed on rated load (JEDEC method) T _C =60℃		I _{FSM}	60							Amps
Maximum Instantaneous Forward Voltage Drop Per element at 1.5A		V _F	1.0							Volts
Rating for Fusing (t<8.3ms)		I ² t	127							A ² s
Maximum Average Reverse Current at rated DC Blocking Voltage	T _A = 25℃	I _R	5.0							μA
	T _A = 125℃		500							
Typical Thermal Resistance per leg (NOTE 1)		R _{θJL}	8.0							℃/W
		R _{θJA}	12							
Operating and Storage Temperature Range		T _J , T _{STG}	(-55 to +150)							℃

Notes: 1. Bolt down on heatsink with silicon thermal compound between bridge and mounting surface for maximum heat transfer with #6 screw.
2. Unit mounted 1.0" x 4.0" x 0.11" thick (10.5 x 10.5 x 0.3cm) A1 Plate
3. Unit mounted on P.C.B. at 0.375" (9.5mm) lead with 0.5" x 0.5" (12 x 12mm) copper pads



GLASS PASSIVATED SINGLE-PHASE BRIDGE RECTIFIER

GBPC1005 THRU GBPC110

RATINGS AND CHARACTERISTICS CURVES GBPC1005 THRU GBPC110

FIG. 1 - DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG




FIG. 3 - TYPICAL FORWARD CHARACTERISTICS PER LEG




FIG. 4 - TYPICAL REVERSE LEAKAGE CHARACTERISTICS PER LEG




FIG. 5 - TYPICAL JUNCTION CAPACITANCE PER LEG




FIG. 6 - TYPICAL TRANSIENT THERMAL IMPEDANCE PER LEG

