



HIGH EFFICIENCY GLASS PASSIVATED RECTIFIER

HER151G THRU HER158G

VOLTAGE RANGE

50 to 1000 Volts

CURRENT


1.5 Ampere

FEATURES

- Glass passivated chip junction
- Low power loss, high efficiency
- Low leakage
- High speed switching
- High surge capacity
- High temperature soldering guaranteed
260°C/10 seconds, 0.375" (9.5mm) lead length

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-0 rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.014ounce, 0.39 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

		SYMBOLS	HER 151G	HER 152G	HER 153G	HER 154G	HER 155G	HER 156G	HER 157G	HER 158G	UNIT
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	50	100	200	300	400	600	800	1000	Volts
Maximum RMS Voltage		V _{RMS}	35	70	140	210	280	420	560	700	Volts
Maximum DC Blocking Voltage		V _{DC}	50	100	200	300	400	600	800	1000	Volts
Maximum Average Forward Rectified Current 0.375 " (9.5mm) lead length at T _A =50℃		I _(AV)	1.5								Amps
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)		I _{FSM}	50								Amps
Maximum Instantaneous Forward Voltage at 1.5A		V _F	1.0			1.3		1.5	1.7		Volts
Maximum DC Reverse Current at rated DC Blocking Voltage at	T _A = 25℃	I _R	5.0								μA
	T _A = 125℃		250								
Maximum Full Load Reverse Current, full cycle average 0.375 " (9.5mm) lead length at T _L =55℃		I _{R(AV)}	100								μA
Maximum Reverse Recovery Time Test conditions I _F =0.5A, I _R =1.0A, I _{RR} =0.25A,		t _{rr}	50					75			nS
Typical Junction Capacitance (NOTE 2)		C _J	30						20		pF
Typical Thermal Resistance (NOTE 1)		R _{θJA}	40								℃/W
Operating Junction Temperature Range		T _J	(-55 to +150)								℃
Storage Temperature Range		T _{STG}	(-55 to +150)								℃

Notes:

1. Thermal Resistance from Junction to ambient with 0.375" (9.5mm) lead length, PCB mounted.
2. Measured at 1.0MHz and applied reverse voltage of 4.0V



HIGH EFFICIENCY GLASS PASSIVATED RECTIFIER

HER151G THRU HER158G

VOLTAGE RANGE	50 to 1000 Volts
CURRENT	1.5 Ampere

RATING AND CHARACTERISTIC CURVES HER151G THRU HER158G

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE





FIG.6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTES : 1. Rise Time=7ns max. Input Impedance= 1 megohm, 22pF
2. Rise time=10ns max. Source Impedance= 50 ohms

SET TIME BASE FOR 50/100ns/cm