




VOLTAGE RANGE	50 to 1000 Volts
CURRENT	15 Amperes

- | Low cost
- | This series is UL recognized under component index, file number E127707
- | High forward surge current capability
- | Integrally molded heatsink provide very low thermal resistance
- | High isolation voltage from case to lugs
- | High temperature soldering guaranteed:
260°C/10 second, at 5 lbs. (2.3kg) tension.

- ! Case: Molded plastic body
- ! Terminal: Lead solderable per MIL-STD-202E method 208C.
- ! Polarity: Polarity symbols molded on case
- ! Mounting: Thru hole for #6 screw, 5.0 in.-lbs torque max.
- ! Weight: 0.20ounce, 5.62 grams



For capacitive load derate current by 20%.

	SYMBOLS	KBPC 15005N	KBPC 1501N	KBPC 1502N	KBPC 1504N	KBPC 1506N	KBPC 1508N	KBPC 1510N	UNITS	
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	Volts	
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	Volts	
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	Volts	
Maximum Average Forward Rectified Output Current, at T _C =55℃(Note1, 2)	I _(AV)	15							Amps	
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	300							Amps	
Rating for Fusing(t<8.3ms)	I ² T	373							A ² S	
Maximum Instantaneous Forward Voltage at 7.5A	V _F	1.1							Volts	
Maximum DC Reverse Current at rated DC blocking voltage	T _A =25℃	I _R	10							μAmps
	T _A =150℃		1.0							mAmps
Isolation Voltage from case to leads	V _{ISO}	2500							V _{AC}	
Typical Thermal Resistance (Note 1)	R _{θJC}	2.0							℃/W	
Operating Temperature Range	T _J	-55 to +150							℃	
Storage Temperature Range	T _{STG}	-55 to +150							℃	

- Unit mounted on 5"×4"×3" thick (12.8mm×10.2mm×7.3mm) Al. plate.
- Bolt down on heat-sink with silicone thermal compound between bridge and mounting surface for maximum heat transfer efficiency with #10 screw.



MASTER INSTRUMENT CORPORATION

SINGLE-PHASE BRIDGE RECTIFIER
KBPC15005N THRU KBPC1510N

VOLTAGE RANGE 50 to 1000 Volts
CURRENT 15 Amperes

RATINGS AND CHARACTERISTIC CURVES KBPC15005N THRU KBPC1510N

