

# C106 Series

## Sensitive Gate Silicon Controlled Rectifiers Reverse Blocking Thyristors

Glassivated PNP devices designed for high volume consumer applications such as temperature, light, and speed control; process and remote control, and warning systems where reliability of operation is important.

### Features

- Glassivated Surface for Reliability and Uniformity
- Power Rated at Economical Prices
- Practical Level Triggering and Holding Characteristics
- Flat, Rugged, Thermopad Construction for Low Thermal Resistance, High Heat Dissipation and Durability
- Sensitive Gate Triggering
- These are Pb-Free Devices

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Max	Unit
Peak Repetitive Off-State Voltage (Note 1) (Sine Wave, 50–60 Hz, $R_{GK} = 1\text{ k}\Omega$ , $T_C = -40^\circ$ to $110^\circ\text{C}$ )	$V_{DRM}$ , $V_{RRM}$		V
	C106B	200	
	C106D, C106D1*	400	
	C106M, C106M1*	600	
On-State RMS Current ( $180^\circ$ Conduction Angles, $T_C = 80^\circ\text{C}$ )	$I_{T(RMS)}$	4.0	A
Average On-State Current ( $180^\circ$ Conduction Angles, $T_C = 80^\circ\text{C}$ )	$I_{T(AV)}$	2.55	A
Peak Non-Repetitive Surge Current (1/2 Cycle, Sine Wave, 60 Hz, $T_J = +25^\circ\text{C}$ )	$I_{TSM}$	20	A
Circuit Fusing Considerations ( $t = 8.3\text{ ms}$ )	$I^2t$	1.65	$\text{A}^2\text{s}$
Forward Peak Gate Power (Pulse Width $\leq 1.0\ \mu\text{sec}$ , $T_C = 80^\circ\text{C}$ )	$P_{GM}$	0.5	W
Forward Average Gate Power (Pulse Width $\leq 1.0\ \mu\text{sec}$ , $T_C = 80^\circ\text{C}$ )	$P_{G(AV)}$	0.1	W
Forward Peak Gate Current (Pulse Width $\leq 1.0\ \mu\text{sec}$ , $T_C = 80^\circ\text{C}$ )	$I_{GM}$	0.2	A
Operating Junction Temperature Range	$T_J$	-40 to +110	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	-40 to +150	$^\circ\text{C}$
Mounting Torque (Note 2)	-	6.0	in. lb.

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.


1.  $V_{DRM}$  and  $V_{RRM}$  for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.
2. Torque rating applies with use of compression washer (B52200F006). Mounting torque in excess of 6 in. lb. does not appreciably lower case-to-sink thermal resistance. Anode lead and heatsink contact pad are common.



ON Semiconductor®

<http://onsemi.com>

SCRs  
4 A RMS, 200 – 600 Volts



TO-225AA  
CASE 077  
STYLE 2

### MARKING DIAGRAM & PIN ASSIGNMENT



Y = Year  
WW = Work Week  
C106xx = Device Code  
xx = B, D, D1, M, M1  
G = Pb-Free Package

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

## C106 Series

### Thermal Characteristics (T<sub>C</sub> = 25°C unless otherwise noted.)

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction-to-Case	R <sub>θJC</sub>	3.0	°C/W
Thermal Resistance, Junction-to-Ambient	R <sub>θJA</sub>	75	°C/W
Maximum Lead Temperature for Soldering Purposes 1/8 in. from Case for 10 Seconds	T <sub>L</sub>	260	°C

### Electrical Characteristics (T<sub>C</sub> = 25°C unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

#### OFF CHARACTERISTICS

Peak Repetitive Forward or Reverse Blocking Current (V <sub>AK</sub> = Rated V <sub>DRM</sub> or V <sub>R<sub>RRM</sub></sub> , R <sub>GK</sub> = 1 kΩ)	I <sub>DRM</sub> , I <sub>R<sub>RRM</sub></sub>	T <sub>J</sub> = 25°C	-	-	10	μA
		T <sub>J</sub> = 110°C	-	-	100	μA

#### ON CHARACTERISTICS

Peak Forward On-State Voltage (Note 3) (I <sub>TM</sub> = 4 A)	V <sub>TM</sub>	-	-	2.2	V	
Gate Trigger Current (Continuous dc) (Note 4) (V <sub>AK</sub> = 6 Vdc, R <sub>L</sub> = 100 Ω)	I <sub>GT</sub>	T <sub>J</sub> = 25°C	-	15	200	μA
		T <sub>J</sub> = -40°C	-	35	500	
Peak Reverse Gate Voltage (I <sub>GR</sub> = 10 μA)	V <sub>G<sub>RM</sub></sub>	-	-	6.0	V	
Gate Trigger Voltage (Continuous dc) (Note 4) (V <sub>AK</sub> = 6 Vdc, R <sub>L</sub> = 100 Ω)	V <sub>GT</sub>	T <sub>J</sub> = 25°C	0.4	0.60	0.8	V
		T <sub>J</sub> = -40°C	0.5	0.75	1.0	
Gate Non-Trigger Voltage (Continuous dc) (Note 4) (V <sub>AK</sub> = 12 V, R <sub>L</sub> = 100 Ω, T <sub>J</sub> = 110°C)	V <sub>GD</sub>	0.2	-	-	V	
Latching Current (V <sub>AK</sub> = 12 V, I <sub>G</sub> = 20 mA, R <sub>GK</sub> = 1 kΩ)	I <sub>L</sub>	T <sub>J</sub> = 25°C	-	0.20	5.0	mA
		T <sub>J</sub> = -40°C	-	0.35	7.0	
Holding Current (V <sub>D</sub> = 12 Vdc) (Initiating Current = 20 mA, R <sub>GK</sub> = 1 kΩ)	I <sub>H</sub>	T <sub>J</sub> = 25°C	-	0.19	3.0	mA
		T <sub>J</sub> = -40°C	-	0.33	6.0	
		T <sub>J</sub> = +110°C	-	0.07	2.0	

#### DYNAMIC CHARACTERISTICS

Critical Rate-of-Rise of Off-State Voltage (V <sub>AK</sub> = Rated V <sub>DRM</sub> , Exponential Waveform, R <sub>GK</sub> = 1 kΩ, T <sub>J</sub> = 110°C)	dv/dt	-	8.0	-	V/μs
--	-------	---	-----	---	------

3. Pulse Test: Pulse Width ≤ 2.0 ms, Duty Cycle ≤ 2%.
4. R<sub>GK</sub> is not included in measurement.

# C106 Series

## Voltage Current Characteristic of SCR

Symbol	Parameter
$V_{DRM}$	Peak Repetitive Off State Forward Voltage
$I_{DRM}$	Peak Forward Blocking Current
$V_{RRM}$	Peak Repetitive Off State Reverse Voltage
$I_{RRM}$	Peak Reverse Blocking Current
$V_{TM}$	Peak On State Voltage
$I_H$	Holding Current





Figure 1. Average Current Derating






Figure 2. Maximum On-State Power Dissipation


## C106 Series




**Figure 3. Typical Gate Trigger Current versus Junction Temperature**



**Figure 4. Typical Holding Current versus Junction Temperature**



**Figure 5. Typical Gate Trigger Voltage versus Junction Temperature**




**Figure 6. Typical Latching Current versus Junction Temperature**


# C106 Series

## PACKAGE INTERCHANGEABILITY

The dimensional diagrams below compare the critical dimensions of the ON Semiconductor C-106 package with competitive devices. It has been demonstrated that the smaller dimensions of the ON Semiconductor package make it compatible in most lead-mount and chassis-mount applications. The user is advised to compare all critical dimensions for mounting compatibility.



ON Semiconductor C-106 Package



Competitive C-106 Package

### ORDERING INFORMATION


Device	Package	Shipping†
C106BG	TO-225AA (Pb-Free)	500 Units / Box
C106DG	TO-225AA (Pb-Free)	500 Units / Box
C106D1G*	TO-225AA (Pb-Free)	500 Units / Box
C106MG	TO-225AA (Pb-Free)	500 Units / Box
C106M1G*	TO-225AA (Pb-Free)	500 Units / Box

\*D1 signifies European equivalent for D suffix and M1 signifies European equivalent for M suffix.

# C106 Series

## PACKAGE DIMENSIONS

TO-225  
CASE 77-09  
ISSUE Z



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 077-01 THRU -08 OBSOLETE, NEW STANDARD 077-09.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.425	0.435	10.80	11.04
B	0.295	0.305	7.50	7.74
C	0.095	0.105	2.42	2.66
D	0.020	0.026	0.51	0.66
F	0.115	0.130	2.93	3.30
G	0.094 BSC		2.39 BSC	
H	0.050	0.095	1.27	2.41
J	0.015	0.025	0.39	0.63
K	0.575	0.655	14.61	16.63
M	5° TYP		5° TYP	
Q	0.148	0.158	3.76	4.01
R	0.045	0.065	1.15	1.65
S	0.025	0.035	0.64	0.88
U	0.145	0.155	3.69	3.93
V	0.040	---	1.02	---

STYLE 2:

1. CATHODE
2. ANODE
3. GATE

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative