

# NLSV8T244

## 8-Bit Dual-Supply Non-Inverting Level Translator

The NLSV8T244 is a 8-bit configurable dual-supply voltage level translator. The input  $A_n$  and output  $B_n$  ports are designed to track two different power supply rails,  $V_{CCA}$  and  $V_{CCB}$  respectively. Both supply rails are configurable from 0.9 V to 4.5 V allowing universal low-voltage translation from the input  $A_n$  to the output  $B_n$  port.

### Features

- Wide  $V_{CCA}$  and  $V_{CCB}$  Operating Range: 0.9 V to 4.5 V
- High-Speed w/ Balanced Propagation Delay
- Inputs and Outputs have OVT Protection to 4.5 V
- Non-preferential  $V_{CCA}$  and  $V_{CCB}$  Sequencing
- Outputs at 3-State until Active  $V_{CC}$  is Reached
- Power-Off Protection
- Outputs Switch to 3-State with  $V_{CCB}$  at GND
- Ultra-Small Packaging: 4.0 mm x 2.0 mm UDFN20
- This is a Pb-Free Device

### Typical Applications

- Mobile Phones, PDAs, Other Portable Devices

### Important Information

- ESD Protection for All Pins:

HBM (Human Body Model) > 6000 V




Figure 1. Logic Diagram



ON Semiconductor®

<http://onsemi.com>



MARKING  
DIAGRAM



UDFN20  
MU SUFFIX  
CASE 517AK

LC = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

### PIN ASSIGNMENT

$V_{CCA}$	1	20	$V_{CCB}$
A1	2	19	B1
A2	3	18	B2
A3	4	17	B3
A4	5	16	B4
A5	6	15	B5
A6	7	14	B6
A7	8	13	B7
A8	9	12	B8
GND	10	11	OE

(Top View)

### ORDERING INFORMATION

Device	Package	Shipping <sup>†</sup>
NLSV8T244MUTAG	UDFN20 (Pb-Free)	3000/Tape & Reel

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

# NLSV8T244

## PIN ASSIGNMENT

PIN	FUNCTION
V <sub>CCA</sub>	Input Port DC Power Supply
V <sub>CCB</sub>	Output Port DC Power Supply
GND	Ground
A <sub>n</sub>	Input Port
B <sub>n</sub>	Output Port
OE	Output Enable

## TRUTH TABLE

Inputs		Outputs
OE	A <sub>n</sub>	B <sub>n</sub>
L	L	L
L	H	H
H	X	3-State

## MAXIMUM RATINGS

Symbol	Rating	Value	Condition	Unit
V <sub>CCA</sub> , V <sub>CCB</sub>	DC Supply Voltage	-0.5 to +5.5		V
V <sub>I</sub>	DC Input Voltage	A <sub>n</sub>	-0.5 to +5.5	V
V <sub>C</sub>	Control Input	OE	-0.5 to +5.5	V
V <sub>O</sub>	DC Output Voltage (Power Down)	B <sub>n</sub>	-0.5 to +5.5	V <sub>CCA</sub> = V <sub>CCB</sub> = 0
	(Active Mode)	B <sub>n</sub>	-0.5 to +5.5	V
	(Tri-State Mode)	B <sub>n</sub>	-0.5 to +5.5	V
I <sub>IK</sub>	DC Input Diode Current		-20	VI < GND
I <sub>OK</sub>	DC Output Diode Current		-50	VO < GND
I <sub>O</sub>	DC Output Source/Sink Current		±50	mA
I <sub>CCA</sub> , I <sub>CCB</sub>	DC Supply Current Per Supply Pin		±100	mA
I <sub>GND</sub>	DC Ground Current per Ground Pin		±100	mA
T <sub>STG</sub>	Storage Temperature		-65 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

## RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter	Min	Max	Unit
V <sub>CCA</sub> , V <sub>CCB</sub>	Positive DC Supply Voltage	0.9	4.5	V
V <sub>I</sub>	Bus Input Voltage	GND	4.5	V
V <sub>C</sub>	Control Input	OE	GND	V
V <sub>IO</sub>	Bus Output Voltage (Power Down Mode)	B <sub>n</sub>	GND	V
	(Active Mode)	B <sub>n</sub>	GND	V <sub>CCB</sub>
	(Tri-State Mode)	B <sub>n</sub>	GND	V
T <sub>A</sub>	Operating Temperature Range	-40	+85	°C
Δt / ΔV	Input Transition Rise or Rate V <sub>I</sub> , from 30% to 70% of V <sub>CC</sub> ; V <sub>CC</sub> = 3.3 V ±0.3 V	0	10	nS

## DC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Test Conditions	$V_{CCA}$ (V)	$V_{CCB}$ (V)	-40°C to +85°C		Unit
					Min	Max	
$V_{IH}$	Input HIGH Voltage (An, $\overline{OE}$ )		3.6 – 4.5	0.9 – 4.5	2.2	–	V
			2.7 – 3.6		2.0	–	
			2.3 – 2.7		1.6	–	
			1.4 – 2.3		0.65 * $V_{CCA}$	–	
			0.9 – 1.4		0.9 * $V_{CCA}$	–	
$V_{IL}$	Input LOW Voltage (An, $\overline{OE}$ )		3.6 – 4.5	0.9 – 4.5	–	0.8	V
			2.7 – 3.6		–	0.8	
			2.3 – 2.7		–	0.7	
			1.4 – 2.3		–	0.35 * $V_{CCA}$	
			0.9 – 1.4		–	0.1 * $V_{CCA}$	
$V_{OH}$	Output HIGH Voltage	$I_{OH} = -100 \mu A; V_I = V_{IH}$	0.9 – 4.5	0.9 – 4.5	$V_{CCB} - 0.2$	–	V
			$I_{OH} = -0.5 \text{ mA}; V_I = V_{IH}$	0.9	0.9	0.75 * $V_{CCB}$	
			$I_{OH} = -2 \text{ mA}; V_I = V_{IH}$	1.4	1.4	1.05	
			$I_{OH} = -6 \text{ mA}; V_I = V_{IH}$	1.65	1.65	1.25	
			2.3	2.3	2.0	–	
			$I_{OH} = -12 \text{ mA}; V_I = V_{IH}$	2.3	2.3	1.8	
			2.7	2.7	2.2	–	
			$I_{OH} = -18 \text{ mA}; V_I = V_{IH}$	2.3	2.3	1.7	–
			3.0	3.0	2.4	–	
			$I_{OH} = -24 \text{ mA}; V_I = V_{IH}$	3.0	3.0	2.2	–
$V_{OL}$	Output LOW Voltage	$I_{OL} = 100 \mu A; V_I = V_{IL}$	0.9 – 4.5	0.9 – 4.5	–	0.2	V
			$I_{OL} = 0.5 \text{ mA}; V_I = V_{IL}$	– 1.1 –	– 1.1 –	– 0.3 –	
			$I_{OL} = 2 \text{ mA}; V_I = V_{IL}$	1.4	1.4	– 0.35 –	
			$I_{OL} = 6 \text{ mA}; V_I = V_{IL}$	1.65	1.65	– 0.3 –	
			$I_{OL} = 12 \text{ mA}; V_I = V_{IL}$	2.3	2.3	– 0.4 –	
			2.7	2.7	– 0.4 –		
			$I_{OL} = 18 \text{ mA}; V_I = V_{IL}$	2.3	2.3	– 0.6 –	
			3.0	3.0	– 0.45 –		
			$I_{OL} = 24 \text{ mA}; V_I = V_{IL}$	3.0	3.0	– 0.6 –	
$I_I$	Input Leakage Current	$V_I = V_{CCA}$ or GND	0.9 – 4.5	0.9 – 4.5	-1.0	1.0	$\mu A$
$I_{OFF}$	Power-Off Leakage Current	$\overline{OE} = 0 \text{ V}$	0 0.9 – 4.5	0.9 – 4.5 0	-1.0 -1.0	1.0 1.0	$\mu A$
$I_{CCA}$	Quiescent Supply Current	$V_I = V_{CCA}$ or GND; $I_O = 0$ , $V_{CCA} = V_{CCB}$	0.9 – 4.5	0.9 – 4.5	–	2.0	$\mu A$
$I_{CCB}$	Quiescent Supply Current	$V_I = V_{CCA}$ or GND; $I_O = 0$ , $V_{CCA} = V_{CCB}$	0.9 – 4.5	0.9 – 4.5	–	2.0	$\mu A$
$I_{CCA} + I_{CCB}$	Quiescent Supply Current	$V_I = V_{CCA}$ or GND; $I_O = 0$ , $V_{CCA} = V_{CCB}$	0.9 – 4.5	0.9 – 4.5	–	4.0	$\mu A$
$\Delta I_{CCA}$	Increase in $I_{CC}$ per Input Voltage, Other Inputs at $V_{CCA}$ or GND	$V_I = V_{CCA} - 0.6 \text{ V}$ ; $V_I = V_{CCA}$ or GND	4.5 3.6	4.5 3.6	–	10 5.0	$\mu A$
$\Delta I_{CCB}$	Increase in $I_{CC}$ per Input Voltage, Other Inputs at $V_{CCA}$ or GND	$V_I = V_{CCA} - 0.6 \text{ V}$ ; $V_I = V_{CCA}$ or GND	4.5 3.6	4.5 3.6	–	10 5.0	$\mu A$
$I_{OZ}$	I/O Tri-State Output Leakage Current	$T_A = 25^\circ C$ , $\overline{OE} = 0 \text{ V}$	0.9 – 4.5	0.9 – 4.5	-1.0	1.0	$\mu A$

TOTAL STATIC POWER CONSUMPTION ( $I_{CCA} + I_{CCB}$ )

$V_{CCA}$ (V)	-40°C to +85°C										Unit	
	$V_{CCB}$ (V)											
	4.5		3.3		2.8		1.8		0.9			
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
4.5		2		2		2		2		< 1.5	µA	
3.3		2		2		2		2		< 1.5	µA	
2.8		< 2		< 1		< 1		< 0.5		< 0.5	µA	
1.8		< 1		< 1		< 0.5		< 0.5		< 0.5	µA	
0.9		< 0.5		< 0.5		< 0.5		< 0.5		< 0.5	µA	

NOTE: Connect ground before applying supply voltage  $V_{CCA}$  or  $V_{CCB}$ . This device is designed with the feature that the power-up sequence of  $V_{CCA}$  and  $V_{CCB}$  will not damage the IC.

## AC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	$V_{CCA}$ (V)	-40°C to +85°C										Unit	
			$V_{CCB}$ (V)											
			4.5		3.3		2.8		1.8		1.2			
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
$t_{PLH}, t_{PHL}$ (Note 1)	Propagation Delay, $A_n$ to $B_n$	4.5		1.6		1.8		2.0		2.1		2.3	nS	
		3.3		1.7		1.9		2.1		2.3		2.6		
		2.8		1.9		2.1		2.3		2.5		2.8		
		1.8		2.1		2.4		2.5		2.7		3.0		
		1.2		2.4		2.7		2.8		3.0		3.3		
$t_{PZH}, t_{PZL}$ (Note 1)	Output Enable, $\overline{OE}$ to $B_n$	4.5		2.6		3.8		4.0		4.1		4.3	nS	
		3.3		3.7		3.9		4.1		4.3		4.6		
		2.5		—	—	3.9		4.1		4.3		4.8		
		1.8		4.1		4.4		4.5		4.7		5.0		
		1.2		4.4		4.7		4.8		5.0		5.3		
$t_{PHZ}, t_{PLZ}$ (Note 1)	Output Disable, $\overline{OE}$ to $B_n$	4.5		2.6		3.8		4.0		4.1		4.3	nS	
		3.3		3.7		3.9		4.1		4.3		4.6		
		2.5		3.9		4.1		4.3		4.5		4.8		
		1.8		4.1		4.4		4.5		4.7		5.0		
		1.2		4.4		4.7		4.8		5.0		5.3		
$t_{OSHL}, t_{OSLH}$ (Note 1)	Output to Output Skew, Time	4.5		0.15		0.15		0.15		0.15		0.15	nS	
		3.3		0.15		0.15		0.15		0.15		0.15		
		2.5		0.15		0.15		0.15		0.15		0.15		
		1.8		0.15		0.15		0.15		0.15		0.15		
		1.2		0.15		0.15		0.15		0.15		0.15		

1. Propagation delays defined per Figure 2.

## CAPACITANCE

Symbol	Parameter	Test Conditions	Typ (Note 2)	Unit
$C_{IN}$	Control Pin Input Capacitance	$V_{CCA} = V_{CCB} = 3.3$ V, $V_I = 0$ V or $V_{CCA/B}$	3.5	pF
$C_{I/O}$	I/O Pin Input Capacitance	$V_{CCA} = V_{CCB} = 3.3$ V, $V_I = 0$ V or $V_{CCA/B}$	5.0	pF
$C_{PD}$	Power Dissipation Capacitance	$V_{CCA} = V_{CCB} = 3.3$ V, $V_I = 0$ V or $V_{CCA}$ , $f = 10$ MHz	20	pF

2. Typical values are at  $T_A = +25^\circ\text{C}$ .

3.  $C_{PD}$  is defined as the value of the IC's equivalent capacitance from which the operating current can be calculated from:

$$I_{CC(\text{operating})} \cong C_{PD} \times V_{CC} \times f_{IN} \times N_{SW} \text{ where } I_{CC} = I_{CCA} + I_{CCB} \text{ and } N_{SW} = \text{total number of outputs switching.}$$

# NLSV8T244




Figure 2. AC (Propagation Delay) Test Circuit

Test	Switch
$t_{PLH}, t_{PHL}$	OPEN
$t_{PLZ}, t_{PZL}$	$V_{CCO} \times 2$
$t_{PHZ}, t_{PZH}$	GND

$C_L = 15 \text{ pF}$  or equivalent (includes probe and jig capacitance)  
 $R_L = 2 \text{ k}\Omega$  or equivalent  
 $Z_{OUT}$  of pulse generator =  $50 \Omega$






Figure 3. AC (Propagation Delay) Test Circuit Waveforms

Symbol	$V_{CC}$				
	3.0 V – 4.5 V	2.3 V – 2.7 V	1.65 V – 1.95 V	1.4 V – 1.6 V	0.9 V – 1.3 V
$V_{mA}$	$V_{CCA}/2$	$V_{CCA}/2$	$V_{CCA}/2$	$V_{CCA}/2$	$V_{CCA}/2$
$V_{mB}$	$V_{CCB}/2$	$V_{CCB}/2$	$V_{CCB}/2$	$V_{CCB}/2$	$V_{CCB}/2$
$V_X$	$V_{OL} \times 0.1$				
$V_Y$	$V_{OH} \times 0.9$				


## PACKAGE DIMENSIONS

UDFN20 4x2, 0.4P  
CASE 517AK-01  
ISSUE O

## NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSIONS b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM TERMINAL TIP.
4. MOLD FLASH ALLOWED ON TERMINALS ALONG EDGE OF PACKAGE. FLASH MAY NOT EXCEED 0.03 ONTO BOTTOM SURFACE OF TERMINALS.
5. DETAIL A SHOWS OPTIONAL CONSTRUCTION FOR TERMINALS.

MILLIMETERS		
DIM	MIN	MAX
A	0.45	0.55
A1	0.00	0.05
A3	0.13 REF	
b	0.15	0.25
D	4.00 BSC	
E	2.00 BSC	
e	0.40 BSC	
L	0.50	0.60
L1	0.00	0.03
L2	0.60	0.70

MOUNTING FOOTPRINT  
SOLDERMASK DEFINED

DIMENSIONS: MILLIMETERS

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

## LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

## N. American Technical Support: 800-282-9855 Toll Free

USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative