



Data Sheet

Features



- For broadband applications
- Typical 3dB bandwidth of 3.8 MHz
- High attenuation
- Single-ended operation
- Ceramic Surface Mount Package (SMP)
- Replaces Sawtek Part 851549 (BW 3dB=3.5MHz)
- Hermetic
- RoHS compliant (2002/95/EC), Pb-free 



Package Pin Configuration

Surface Mount 15.3 x 6.50 x 1.50 mm

Bottom View



Pin No.	Description
5	Output
10	Input
1,6	Ground
2,3,4,7,8,9	Case ground

Dimensions shown are nominal in millimeters
 All tolerances are ± 0.15 mm except overall
 length and width $+0.15$ mm/ -0.10 mm

Body: Al_2O_3 ceramic
 Lid: Kovar, Ni plated
 Terminations: Au plating 0.5 - 1.0 μ m,
 over a 2 - 6 μ m Ni plating

Data Sheet
Electrical Specifications ⁽¹⁾

 Operating Temperature Range: ⁽²⁾ 0 to +70 °C


Parameter ⁽³⁾	Minimum	Typical	Maximum	Unit
Center Frequency	-	70	-	MHz
Minimum Insertion Loss	-	19	22	dB
Lower 1 dB Bandedge ⁽⁴⁾	-	68.35	68.6	MHz
Upper 1 dB Bandedge	71.4	71.68	-	MHz
Lower 3 dB Bandedge ⁽⁴⁾	-	68.12	68.2	MHz
Upper 3 dB Bandedge	71.8	71.92	-	MHz
Lower 40 dB Bandedge ⁽⁴⁾	67	67.31	-	MHz
Upper 40 dB Bandedge	-	72.75	73	MHz
Amplitude Variation 68.6 - 71.4 MHz	-	0.6	1	dB p-p
Phase Linearity 68.6 - 71.4 MHz	-	3.5	6	deg p-p
Group Delay Variation 68.6 - 71.4 MHz	-	84	150	nsec
Absolute Delay	-	2.03	-	µsec
Relative Attenuation ⁽⁴⁾				
10 - 30 MHz	50	58	-	dB
30 - 66.7 MHz	44	49	-	dB
73.3 - 110 MHz	40	46	-	dB
110 - 200 MHz	50	60	-	dB
Source Impedance: ⁽⁵⁾	-	50	-	Ω
Load Impedance: ⁽⁵⁾	-	50	-	Ω
Substrate Material	-	LiTaO ₃	-	-
Temperature Coefficient of Frequency	-	-23	-	ppm/°C

Notes:

1. All specifications are based on the test circuit shown below
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. All attenuation measurements are measured relative to minimum insertion loss
5. This is the optimum impedance in order to achieve the performance shown





Test Circuit:

Actual matching values may vary due to PCB layout and parasitics




Data Sheet


Typical Performance (at +25°C)



Input Smith Chart



Output Smith Chart




Data Sheet

Maximum Ratings


Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating Temperature Range	T	0	+25	+70	°C
Storage Temperature Range	T _{stg}	-40	-	+85	°C

Important Notes

Warnings

- Electrostatic Sensitive Device (ESD) 
- Avoid ultrasonic exposure

RoHS Compliance

- This product complies with EU directive 2002/95/EC (RoHS) 

Solderability

- Compatible with JEDEC J-STD-020C **Pb-free** process, **260°C** peak reflow temperature ([see soldering profile](#))

Links to Additional Technical Information

[PCB Layout Tips](#)

[Qualification Flowchart](#)

[Soldering Profile](#)

[S-Parameters](#)

[RoHS Information](#)

[Other Technical Information](#)

Sawtek's liability is limited only to the Surface Acoustic Wave (SAW) component(s) described in this data sheet. Sawtek does not accept any liability for applications, processes, circuits or assemblies, which are implemented using any Sawtek component described in this data sheet.

Contact Information



PO Box 609501
 Orlando, FL 32860-9501
 USA

Phone: +1 (407) 886-8860
 Fax: +1 (407) 886-7061
 Email: custservice@sawtek.com
 Web: www.sawtek.com

Or contact one of our worldwide
 Network of [sales offices](#),
[representatives or distributors](#)