## MLP25L 5x6, Packing Drawing




## **Packing Description:**


MLP25L 5x6 products are classified under Moisture Sensitive Level 1 at 260 °C peak package body temperature.

The carrier tape is made from dissipative polystyrene or polycarbonate resin. The cover tape is a multilayer film primarily composed of polyester film, adhesive layer, heat activated sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3000 units per 330 mm diameter reel. The reels is made of polystyrene plastic (anti-static coated or intrinsic).


These full reels are individually barcode labeled and placed inside a pizza box made of recyclable corrugated brown paper with a Fairchild logo printing. The reel is packed single reel in the pizza box. And these pizza boxes are placed inside a barcode labeled shipping box which comes in different sizes depending on the number of parts shipped.



## Tape Leader and Trailer Configuration




## **MLP Embossed Tape Dimension**




Package	Ao +/-0.10	Bo +/-0.10	D +/-0.05	D <sub>1</sub> min.	E +/-0.1	F +/-0.1	Ko +/-0.1	P <sub>1</sub> TYP	Po TYP	P <sub>2</sub> +/-0/05	T TYP	Tc +/-0.005	W +/-0.3	Wc TYP
MLP25A	5.30	6.30	1.55	1.5	1.75	5.5	1.00	8.0	4.0	2.0	0.3	0.07	12	9.3

Notes: Ao, Bo, and Ko dimensions are determined with respect to the EIA /Jedec RS-481 rotational and lateral movement requirements (see sketches A, B, and C).

0.5 mm





APPROVALS DRAWN	DATE	FAIR						
DFTG. CHK.		SEMICO	טטטטט	MLP25L	5x6			
ENGR, CHK,		Packing Configuration						
					<b>J</b>			
PROJECTIO	SCALE	SIZE	DRAWING NUMBER	REV				
	1:1	N/A	PKG - MLP25A					
INCH [MM]	DO NOT SCALE DRAWING SHEET 1 of							