

NOTES:

- 1) All resistors are 1%, 1/10W, 0603 unless otherwise specified.
- 2) All capacitors are 0.1uF, 10%, 50V, 0603 unless otherwise specified.
- 3) U1 LGA: Populate C2 and C4.  
U2 Socket: Populate C3 and C5; mounted on solder copper side.
- 4) U2 socket: Loranger, 03742 171 6218B.

COMPANY: <b>Kionix Inc.</b>			
TITLE: <b>KX023 Evaluation Board</b>			
DRAWN: Bob Ross	DATED: 3/14/13	CODE: DWG861	SIZE: B
CHECKED:	DATED:	DRAWING NO: KAMMDM001R57	REV: 0
QUALITY CONTROL:	DATED:	SCALE: NONE	
RELEASED:	DATED:	SHEET: 1 OF 2	

A

A

6

5

4

3

2

1

D

D

C


C

B

B

A

REVISION RECORD						CHECKED BY:	DATE:
DATE:	DRAWN BY:	DESCRIPTION:					
3/14/13	Bob Ross	Initial release.					

 MTHOLE1 MTHOLE150 MTHOLE2 MTHOLE150 MTHOLE3 MTHOLE150 MTHOLE4 MTHOLE150	COMPANY:		<b>Kionix Inc.</b>			
			TITLE:			
			KX023 Evaluation Board			
	DRAWN:	DATED:	CODE:	SIZE:	DRAWING NO:	REV:
Bob Ross	3/14/13	DWG861	B	KAMMDM001R57	0	
CHECKED:	DATED:					
QUALITY CONTROL:	DATED:					
RELEASED:	DATED:					
		SCALE: NONE			SHEET: 2 OF 2	