



# Power Management Solutions for Xilinx® FPGAs



Virtex®-5							Core Voltage: 1.0 V
Input Supply	≤200 mA	≤500 mA	≤1 to 1.5 A	≤2 to 2.5 A	≤3 to 5 A	≤25 A	
2.5 to 5.5 V	NCP584 Linear NCP590 Linear NCP1521/2/3 Buck Controller NCP5211 Buck Controller NCP1529 Buck Controller	NCP1521/2/3 Buck Controller NCP5211 Buck Controller NCP1529 Buck Controller	NCP565 Linear NCP5661 Linear NCP5211 Buck Controller NCP1595 Buck Controller	NCP5662 Linear NCP5211 Buck Controller	NCP5663 Linear NCP5211 Buck Controller NCP3101 Buck Converter	NCP1582/3/6 Buck Controller NCP3102 Buck Converter	
≤24 V	NCP5211 Buck Controller	NCP5211 Buck Controller	NCP5211 Buck Controller	NCP5211 Buck Controller	NCP5211 Buck Controller NCP3101 Buck Converter	NCP1582/3/6 Buck Controller NCP3102 Buck Converter	
Virtex-4, Spartan™-3, Spartan-3A, Spartan-3E							Core Voltage: 1.2 V
1.8 V	NCP584 Linear	–	–	–	–	–	
2.5 to 5.5 V	NCP590 Linear NCP584 Linear NCP5211 Buck Controller NCP1521/2/3 Buck Converter	NCP565 Linear NCP5661 Linear NCP5211 Buck Controller NCP1521/2/3 Buck Converter	NCP565 Linear NCP5661 Linear NCP5211 Buck Controller	NCP5662 Linear NCP5211 Buck Controller	NCP5663 Linear NCP5211 Buck Controller NCP3101 Buck Converter	NCP1582/3/6 Buck Controller NCP3102 Buck Converter	
≤24 V	NCP5211 Buck Controller	NCP5211 Buck Controller	NCP5211 Buck Controller NCP3120/2 Buck Converter	NCP5211 Buck Controller NCP3121/3 Buck Converter	NCP5211 Buck Controller NCP3101 Buck Converter	NCP1582/3/6 Buck Controller NCP3102 Buck Converter	
Virtex-II Pro, Virtex-II							Core Voltage: 1.5 V
1.8 V	NCP603 Linear NCP699 Linear	NCP605/6 Linear	–	–	–	–	
2.5 to 5.5 V	NCP590 Linear NCP603 Linear NCP699 Linear NCP1521/2/3 Buck Converter	NCP605/6 Linear NCP1521/2/3 Buck Converter	NCP565 Linear NCP5661 Linear NCP3163 Buck Converter CS51031 Buck Controller	NCP5662 Linear NCP3163 Buck Converter CS51031 Buck Controller	NCP5663 Linear NCP630 Linear CS51031 Buck Controller NCP3101 Buck Converter	NCP3102 Buck Converter	
≤12 V	NCP551 Linear NCP3163 Buck Converter CS51033 Buck Controller	NCP3335 Linear NCP5500 Linear NCP3163 Buck Converter CS51033 Buck Converter	NCP565 Linear NCP5661 Linear CS51413 Buck Converter CS51033 Buck Controller NCP3120/2 Buck Converter	NCP3163 Buck Converter CS51033 Buck Controller NCP3121/3 Buck Converter	NCP5211 Buck Controller CS51033 Buck Controller NCP3101 Buck Converter	NCP1582/3/6 Buck Controller NCP3102 Buck Converter	
≤24 V	LM2931 Linear NCP3163 Buck Converter LM2574 Buck Converter	NCP3163 Buck Converter LM2574 Buck Converter	CS51413 Buck Converter LM2574 Buck Converter	NCP3163 Buck Converter LM2576 Buck Converter	CS51033 Buck Controller	–	
Virtex-E, Spartan-II-E, CoolRunner®-II, CoolRunner-IIA							Core Voltage: 1.8 V
2.5 to 5.5 V	NCP590 Linear NCP603 Linear NCP699 Linear NCP1521/2/3 Buck Converter	NCP605/6 Linear NCP1521/2/3 Buck Converter	NCP565 Linear NCP5661 Linear NCP3163 Buck Converter	NCP5662 Linear NCP1550 Buck Controller NCP3163 Buck Converter	NCP5663 Linear NCP630 Linear CS51031 Buck Controller NCP3101 Buck Converter	NCP3102 Buck Converter	
≤12 V	NCP551 Linear NCP699 Linear NCP3163 Buck Converter CS51033 Buck Controller	NCP3335 Linear NCP5500 Linear NCP3163 Buck Converter CS51033 Buck Controller	NCP565 Linear NCP5661 Linear CS51413 Buck Converter CS51033 Buck Controller NCP3120/2 Buck Converter	NCP3163 Buck Converter LM2576 Buck Converter NCP3121/3 Buck Converter	CS51031 Buck Controller NCP5211 Buck Controller NCP3101 Buck Converter	NCP1582/3/6 Buck Controller NCP3102 Buck Converter	
≤24 V	LM2391 Linear NCP3163 Buck Converter LM2574 Buck Converter	NCP3163 Buck Converter LM2574 Buck Converter	CS51413 Buck Converter LM2574 Buck Converter	NCP3163 Buck Converter LM2576 Buck Converter	CS51033 Buck Controller	–	
Spartan-II, XC9500XV							Core Voltage: 2.5 V
1.8 to 2.5 V	NCP1410 Boost Converter NCP1423 Boost Converter	NCP1421 Boost Converter NCP1422 Boost Converter	–	–	–	–	
3 to 5.5 V	NCP590 Linear NCP603 Linear NCP699 Linear NCP1521/2/3 Buck Converter	NCP605/6 Linear NCP1521/2/3 Buck Converter	NCP565 Linear NCP5661 Linear NCP3163 Buck Converter	NCP5662 Linear NCP1550 Buck Controller NCP3163 Buck Converter	NCP5663/6 Linear NCP630 Linear CS51031 Buck Controller NCP3101 Buck Converter	NCP3102 Buck Converter	
≤12 V	NCP551 Linear NCP3063 Buck Converter LM2574 Buck Converter	NCP3335 Linear NCP5500 Linear NCP3063 Buck Converter LM2574 Buck Converter	NCP565 Linear NCP5661 Linear CS51413 Buck Converter CS51033 Buck Controller NCP3120/2 Buck Converter	NCP3163 Buck Converter LM2576 Buck Converter NCP3121/3 Buck Converter	NCP5663/6 Linear CS51031 Buck Controller NCP5211 Buck Controller NCP3101 Buck Converter	NCP1582/3/6 Buck Controller NCP3102 Buck Converter	
≤24 V	LM2391 Linear NCP3063 Buck Converter LM2574 Buck Converter	NCP3063 Buck Converter LM2574 Buck Converter	CS51413 Buck Converter LM2574 Buck Converter	NCP3163 Buck Converter LM2576 Buck Converter	CS51033 Buck Controller	–	

CoolRunner XPLA3, XC9500XL						Core Voltage: 3.3 V
Input Supply	≤200 mA	≤500 mA	≤1 to 1.5 A	≤2 to 2.5 A	≤3 to 5 A	≤25 A
1.8 to 3 V	NCP1402 Boost Converter NCP1410 Boost Converter NCP1423 Boost Converter	NCP1421 Boost Converter NCP1422 Boost Converter NCP1450A Boost Converter	–	–	–	–
3 to 3.6 V	NCP1521/2/3 Buck Converter NCP3063 Buck Converter	NCP1521/2/3 Buck Converter NCP3063 Buck Converter	NCP3163 Buck/Boost	NCP3163 Buck/Boost	NCP3101 Buck Converter	NCP3102 Buck Converter
3.3 to 5.5 V	NCP590 Linear NCP603 Linear NCP699 Linear NCP1521/2/3 Buck Converter NCP3063 Buck Converter	NCP3335 Linear NCP5500/1 Linear NCP1521/2/3 Buck Converter NCP3063 Buck Converter	NCP565 Linear NCP1117 Linear NCP5661 Linear NCP3163 Buck Converter	NCP5662 Linear NCP1550 Buck Controller NCP3163 Buck Converter	NCP5663 Linear NCP630 Linear CS51031 Buck Controller NCP3101 Buck Converter	NCP3102 Buck Converter
≤12 V	NCP551 Linear NCP3063 Buck Converter CS51033 Buck Controller	NCP3063 Buck Converter CS51033 Buck Controller	NCP565 Linear NCP5661 Linear CS51413 Buck Converter CS51033 Buck Controller NCP3120/2 Buck Converter	NCP3163 Buck Converter LM2576 Buck Converter NCP3121/3 Buck Converter	CS51031 Buck Controller NCP5211 Buck Controller NCP3101 Buck Converter	NCP1582/3/6 Buck Controller NCP3102 Buck Converter
≤24 V	LM2931 Linear NCP3063 Buck Converter LM2574 Buck Converter	NCP3063 Buck Converter LM2574 Buck Converter	CS51413 Buck Converter LM2574 Buck Converter	NCP3163 Buck Converter LM2576 Buck Converter	CS51033 Buck Controller	–
XC9500						Core Voltage: 5.0 V
1.8 V	NCP1402 Boost Converter NCP1410 Boost Converter	NCP1421 Boost Converter NCP1422 Boost Converter NCP1450A Boost Converter	–	–	–	–
2.5 to 4.5 V	NCP1402 Boost Converter NCP1410 Boost Converter	NCP1421 Boost Converter NCP1422 Boost Converter NCP1450A Boost Converter	NCP3163 Buck Converter	NCP3163 Buck Converter	NCP1442 Boost Converter CS51033 Buck Controller NCP3101 Buck Converter	NCP3102 Buck Converter
4.5 to 5.5 V	NCP3063 Buck Converter	NCP3063 Buck Converter	NCP3163 Buck Converter	NCP3163 Buck Converter	CS51031 Buck Controller NCP3101 Buck Converter	NCP3102 Buck Converter
≤12 V	NCP3063 Buck Converter LM2574 Buck Converter	NCP3063 Buck Converter LM2574 Buck Converter	NCP565 Linear NCP5661 Linear CS51413 Buck Converter CS51033 Buck Controller NCP3120/2 Buck Converter	NCP5662 Linear NCP3163 Buck Converter LM2576 Buck Converter NCP3121/3 Buck Converter	NCP5663/6/7 Linear CS51031 Buck Controller NCP5211 Buck Controller NCP3101 Buck Converter	NCP1582/3/6 Buck Controller NCP3102 Buck Converter
≤24 V	NCP3063 Buck Converter LM2574 Buck Converter	NCP3063 Buck Converter LM2574 Buck Converter	CS51413 Buck Converter LM2574 Buck Converter	NCP3163 Buck Converter LM2576 Buck Converter	MC33167 Buck Converter CS51033 Buck Controller	–



Xilinx, the Xilinx logo, Virtex, and CoolRunner are registered trademarks of Xilinx, Inc.; and Spartan is a trademark of Xilinx, Inc.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

**PUBLICATION ORDERING INFORMATION**

**LITERATURE FULFILLMENT:**

Literature Distribution Center for ON Semiconductor  
 P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free  
 USA/Canada.  
**Europe, Middle East and Africa Technical Support:**  
 Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
 Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative